
## Technical information Productnumber : 85935400





## **Product description**

ESD storage trolley with push handle and base made of electrostatically conductive wood fibreboard, edge 7 mm high. Load capacity top shelf 100 kg. Electrostatically conductive version (electrostatic discharge). Suitable for Euro containers of 600x400 mm. Welded steel profile steel, electrostatically conductive, powder coated gray RAL 7015. Equipped with TPE-ESD wheels with precision ball bearing. 2 swivel castors with brake. Complies with EN 1757-3 safety standard for platform trucks.

## Specifications

Article arrangement: New Version: loading surface / HPL plate Walls: open Wheels front: 2 castor wheels solid rubber with wheel locks 125 mm Wheels back: 2 castor wheels solid rubber, 125 mm Colour: grey Surface treatment: powdercoating Internal length (mm): 605 Internal width (mm): 405 Useful height (mm): 400 Weight (kg) 22 Shelf heights: 200/630

Scan the QR code for more information



Type: Fetra ESD trolley Material: electrostatically conductive Floor: closed Subgroup: ESD trolleys Euronorm (mm): 600 x 400 Ral colour: 7015 Length (mm): 750 Width (mm): 415 Height (mm): 970 Loading capacity (kg): 250 Type number: 8593540 EAN Code (Gtin) 8719424076844









