




Technical information

Productnumber : 859393



Product description

ESD-Box cart electrically conductive with double wing door with drive bolt lock. ESD-box cart in angle steel construction with tubular handlebar. Ends, 1 side and top fitted with wire lattice 40 x 40 x 4 mm, completely welded and electrically conductive powder-coated, slate grey RAL 7015. With 2-leaf door of angle steel with welded wire lattice on open side. 1 fixed and 4 detachable shelves made of electrically conductive wooden material according to DIN 68765, light grey. 2 swivel and 2 fixed-wheel castors with ESD-TPE tyres (thermoplastic elastomer), electrically conductive, hubs with precision deep groove ball bearing. Maximum comfort: Very low starting, rolling and swivelling resistance. Low noise operation on level floors. Tyres are non-marking (trackless). TOTALSTOP central braking system standard on swivel castors.

Specifications

Article arrangement: New
Version: lockable/adjustable loading surface
Walls: wire mesh 40*40*4 mm
Top: wire mesh 40*40*4 mm
Subgroup: shelved trolleys
Colour: grey
Surface treatment: powdercoating
Internal length (mm): 1200
Internal width (mm): 780
Loading capacity (kg): 750
Type number: 9392
Additional specifications: rubber wheels with wheel locks

Type: Fetra ESD trolley
Material: electrostatically conductive
Floor: closed
Wheels front: 2 rigid wheels, ESD, rubber, 200 mm
Wheels back: 2 castor wheels, ESD, rubber, 200 mm, with brake
Ral colour: 7015
Length (mm): 1250
Width (mm): 880
Height (mm): 1800
Weight (kg) 175
Shelf heights: 292/582/882/1182/1482
EAN Code (Gtin) 8719424210668

Scan the QR code for more information



KRUIZINGA.NL®
Opslag- en transportmiddelen

KRUIZINGA.DE®
Lager- und Transportmittel

KRUIZINGA.FR®
Stockage et ressources de transport

KRUIZINGA.COM®
Material handling equipment