

Image not found or type unknown



Technical information

Productnumber : 75.184.568.123



Product description

for more information see manual.

Advantages: Versatile use with excellent rolling properties. Low-noise and vibration-damping, streak-free.

Applications: Industrial carts, material handling in factories, waste containers, transport containers, metal and chemical companies, roll containers for medium-heavy loads, tool trolleys, warehouse carts.

Suitable surface: Almost any surface. Uneven surfaces such as clinker bricks, damaged floors and obstacles such as thresholds.

Suitable environment: Dry and not permanently damp. With weak chemicals.

Specifications

Article arrangement: New

Version: Ø 125 mm

Top: base plate 105x85 mm

Bolt hole: Ø 9 mm

Surface treatment: galvanized

Width (mm): 37

Loading capacity (kg): 200

Wheel bearing: ball bearing

Temperature resistance: -20 / +60°C

Type: castor wheel with brake

Material: elastic rubber band

Hole centres: 80x60 mm

Colour: colorless

Length (mm): 125

Height (mm): 155

Weight (kg) 1

Type number: 758456

EAN Code (Gtin) 8719424014259

Scan the QR code for more information



KRUIZINGA.NL®
Opslag- en transportmiddelen

KRUIZINGA.DE®
Lager- und Transportmittel

KRUIZINGA.FR®
Stockage et ressources de transport

KRUIZINGA.COM®
Material handling equipment